

## CLAIM SHEET

61. In an optical scanner having a source of a light beam, a deflector for deflecting said light beam and an imaging lens that focuses the deflected light beam to form a beam spot on a surface to be scanned, the improvement wherein the curvatures in a sub-scanning direction of two of the surfaces of said imaging lens vary continuously along a main scanning direction over the effective area of said imaging lens and independently of the curvatures in the main scanning direction, and wherein the curvatures in the main and sub-scanning directions are non-symmetrical with respect to the optical axis.

62. In an optical scanner having a source of a light beam, a deflector for deflecting said light beam and an imaging lens that focuses the deflected light beam to form a beam spot on a surface to be scanned, the improvement wherein the curvatures in a sub-scanning direction of two of the surfaces of said imaging lens vary continuously along a main scanning direction over the effective area of said imaging lens and independently of the curvatures in the main scanning direction, and wherein the curvatures in the main and sub-scanning directions are non-symmetrical with respect to the optical axis,

wherein the optical magnification of said imaging lens in the sub-scanning direction is constant over the effective scanning region.

70. In an optical scanner having a source of a light beam, a deflector for deflecting said light beam and an imaging lens that focuses the deflected light beam to form a beam spot on a surface to be scanned, the improvement wherein the curvatures in a sub-scanning direction of two of the surfaces of said imaging lens vary continuously along a main scanning direction over the effective area of said imaging lens and independently of

the curvatures in the main scanning direction, and wherein the curvatures in the main and sub-scanning directions are non-symmetrical with respect to the optical axis,

wherein said imaging lens has a surface that is aspheric in the main scanning direction, and

wherein said imaging lens has a surface having a point of inflection in the main scanning direction.

DC\_MAIN 128448 v 2